



### Metric table

1 d <sub>1</sub>	2 d <sub>2</sub> Thread				d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	t	
	VBA	VBA-FP								
25 .98	M 4	M 5	M 6	-	13 .51	7 .28	17 .67	8 .31	9 .35	11 .43
35 1.38	M 6	M 8	M 10	-	18 .71	11 .43	20 .79	8 .31	13 .51	15 .59
45 1.77	M 5*	M 6	M 8	M 10	22 .87	11 .43	26 1.02	12 .47	13 .51	18 .71
55 2.17	M 8	-	-	-	25 .98	13 .51	29 1.14	15 .59	14 .55	18 .71
55 2.17	M 10	-	-	-	25 .98	-	29 1.14	15 .59	15 .59	18 .71
55 2.17	M 12	-	-	-	25 .98	-	29 1.14	15 .59	18 .71	18 .71

Dimensions in: millimeters - inches

\*Only available for VBA

### Specification

- Eight lobed knob  
Nylon plastic
  - Temperature resistant up to 230 °F (110 °C)
  - Glass filled
  - Black, matte finish
- Tapped insert  
Brass, molded-in
- RoHS compliant

### Information

VBA and VBA-FP are economical but durable eight lobed knobs for many applications.

How to order (Blind tapped insert) 1 2 <b>VBA-45-M5</b>	1	Handle diameter d <sub>1</sub>
	2	Thread d <sub>2</sub>
How to order (Through tapped insert) 1 2 <b>VBA-FP-55-M8</b>	1	Handle diameter d <sub>1</sub>
	2	Thread d <sub>2</sub>